


GEHP-1097

ENGINE

Manufacturer	Perkins
Model	4008-TAG2
Power	1177hp (1800rpm) 1207hp (1500rpm)
Cylinder	8 in-line
Displacement	30.561 litres (160 x 190mm)
Compression	13.6 : 1
Aspiration	Turbocharged
Combustion	Direct injection
Consumption	175 l/h (60Hz) 173 l/h (50Hz) at 75% load
Cooling System	Radiator and fan
Filters	Air, fuel and oil
DC System	12V cc (with battery included), alternator and charger
Panel	RPM, hour meter, coolant temperature, oil pressure, manual start
Protection	Engine stopped with overheating and low oil pressure

Perkins



ALTERNATOR

Manufacturer	Heimer
Model	ATED
Type	Synchronous, brushless, 4 poles, 12 leads 3 phase or single phase (optional)
Connection	Star with accessible neutral
Regulation	Electronic voltage regulation within 2%
Cooling System	Shaft mounted fan
Isolation	Class "H"
Bearings	Single or double bearing (available under consult)



POWER

Stand By	1097 kVA - 878 kW / 60 Hz	1125 kVA - 900 kW / 50 Hz
Prime	997 kVA - 798 kW / 60 Hz	1024 kVA - 818 kW / 50 Hz

DIMENSIONS

Open Set	4080mm L x 1650mm W x 2400mm H
Silent Set	6060mm L x 2438mm W x 2590mm H

Base: steel base MIG welded with rubber feet for engine and alternator support for use during about 8 hours. (May be supplied separately if requested).

Silent Enclosure: (optional) Soundproofed to 75dB at 7m or 85dB at 1.5m

AUTOMATIC SWITCHBOARD

Equipped with microprocessed modules of start and stop control and monitoring of engine protection variables.



DPC 560



DKG 307



RGK-60



DS-5520



DS-5510



DS-5560



EGCP-2

Accessories included: Muffler, flexible connection and vibra-stops.
Technical, operation and maintenance manuals, electrical diagrams.

* Pictures for illustrations only.

